

# ERDVARK ENGINEERING (PTY) LTD

## ONEWAY DISC PLOUGH 3 POINT 24", 26" OR 28" - DOP

The Erdvark DOP 3 Point Oneway Disc Plough is ideal for the preparation of seedbed.

Application of shallow cultivation.

This Oneway Disc Plough is used for weed control, as well as moisture retention and the cut in of stubbles and plant remains. Erdvark Bearing Units requires no service or lubrication.

Model No	No Of Disc	Plough Disc Size inches	Working Width m	Mass kg	Plough Disc Spacing mm	Average Tractor Req. kW
DOP9-10-24	10	24"	1.80	550	228	45 - 55
DOP9-10-26	10	26"	1.80	590	228	45 - 55
DOP9-10-28	10	28"	1.80	670	228	45 - 55
DOP9-12-24	12	24"	2.30	624	228	55 - 70
DOP9-12-26	12	26"	2.30	672	228	55 - 70
DOP9-12-28	12	28"	2.30	768	228	55 - 70



It is lubricated with a special lubricant at the factory and sealed and guaranteed that no sand or dust can enter the bearing unit under normal working conditions.

Fitted with 24" (610mm), 26" (660mm) or 28" (710mm) plough discs on heavy duty 45mm axle.

The DOP is fitted with a coulter stabilizer wheel to improve straightness behind tractor and assist with tractor handling.

For queries, contact:

**Willem Oosthuizen**

Mobile: +27 (0) 82 498 6619

Email: [willem@erdvark.co.za](mailto:willem@erdvark.co.za)

**Nico Botes**

Mobile: +27 (0) 82 920 9346

Email: [nico@erdvark.co.za](mailto:nico@erdvark.co.za)

**Dennis Green (Factory Trawal)**

Mobile: +27 (0) 72 120 9159

Office: +27 (0) 27 216 1536

Email: [dennis@erdvark.co.za](mailto:dennis@erdvark.co.za)

Website: [www.erdvark.co.za](http://www.erdvark.co.za)

