

# ERDVARK ENGINEERING (PTY) LTD

## GRADER 3 POINT

The Erdvark 3 Point Grader is ideal for maintaining of farm roads, fire breaks, contours and for the build of new roads. It is also used for levelling of irrigation fields and manure grading. The blade can rotate 180° for backwards pushing. Ideal for manure grading and pushing manure together.

### SPECIFICATION:

Cutting Angles: 15°, 30°, 45°, 60°, 75°, 90°, 180°  
Grader Blade is 200mm high  
Tyres: 185R14

Model No	Description	Mass kg	Working Width Meter	Transport Width Meter	Mouldboard Height Meter	Average Tractor Req. kW
G1 A	Standard Grader	250	1.75	0.900	0.500	25 - 35
G1 B	Standard Grader with Ski-Pads	260	1.75	0.900	0.500	25 - 35
G2 A	Standard Grader	300	2.02	0.900	0.500	25 - 35
G2 B	Standard Grader with Ski-Pads	310	2.02	0.900	0.500	25 - 35
G2 C	Standard Grader with Back Wheel	350	2.02	0.900	0.500	25 - 35
G5 A	Standard Grader	330	2.40	0.900	0.500	25 - 35
G5 B	Standard Grader with Ski-Pads	340	2.40	0.900	0.500	25 - 35
G5 C	Standard Grader with Back Wheel	390	2.40	0.900	0.500	25 - 35
G15 A	Standard Grader	800	2.40	1.100	0.575	35 - 60
G15 B	Standard Grader with Back Wheel	900	2.40	1.100	0.575	35 - 60
G15 AH	Standard Grader with Hydraulic Blade Turn	850	2.40	1.100	0.575	35 - 60
G15 BH	Standard Grader with Back Wheel & Hydraulic Blade Turn	950	2.40	1.100	0.575	35 - 60

G15B



G1B



G5C



G15BH



G15A



For queries, contact:

**Willem Oosthuizen**

Mobile: +27 (0) 82 498 6619

Email: [willem@erdvark.co.za](mailto:willem@erdvark.co.za)

**Nico Botes**

Mobile: +27 (0) 82 920 9346

Email: [nico@erdvark.co.za](mailto:nico@erdvark.co.za)

**Dennis Green (Factory Trawl)**

Mobile: +27 (0) 72 120 9159

Office: +27 (0) 27 216 1536

Email: [dennis@erdvark.co.za](mailto:dennis@erdvark.co.za)

Website: [www.erdvark.co.za](http://www.erdvark.co.za)