

ERDVARK ENGINEERING (PTY) LTD

OFFSET DISC EXTREME HD HINGE TRAILED 36" - HKR

Model No	Disc	Mass Per Disc kg	Working Width m	Disc Spacing mm	Plough Disc Specs	Average Tractor Req. kW
HKR 16-12	12		2.42	410	910 x 12	106 - 126
HKR 16-14	14		2.79	410	910 x 12	124 - 142
HKR 16-16	16		3.15	410	910 x 12	142 - 157
HKR 16-18	18		3.52	410	910 x 12	156 - 171
HKR 16-20	20		3.88	410	910 x 12	165 - 189
HKR 16-22	22		4.25	410	910 x 12	181 - 208
HKR 16-24	24		4.61	410	910 x 12	193 - 228
HKR 16-26	26		4.98	410	910 x 12	209 - 247
HKR 16-28	28		5.34	410	910 x 12	225 - 266
HKR 16-30	30		5.71	410	910 x 12	241 - 285
HKR 16-32	32		6.07	410	910 x 12	257 - 304
HKR 16-34	34		6.44	410	910 x 12	273 - 323
HKR 16-36	36		6.80	410	910 x 12	289 - 343
HKR 18-10	10		2.27	460	910 x 12	106 - 129
HKR 18-12	12		2.68	460	910 x 12	120 - 142
HKR 18-14	14		3.10	460	910 x 12	140 - 159
HKR 18-16	16		3.51	460	910 x 12	159 - 177
HKR 18-18	18		3.92	460	910 x 12	175 - 192
HKR 18-20	20		4.33	460	910 x 12	185 - 213
HKR 18-22	22		4.74	460	910 x 12	204 - 234
HKR 18-24	24		5.15	460	910 x 12	217 - 257
HKR 18-26	26		5.56	460	910 x 12	241 - 276
HKR 18-28	28		5.97	460	910 x 12	259 - 298
HKR 18-30	30		6.38	460	910 x 12	278 - 319
HKR 18-32	32		6.79	460	910 x 12	296 - 340
HKR 20-10	10	380	2.43	510	910 x 12	120 - 146
HKR 20-12	12	380	2.89	510	910 x 12	135 - 160
HKR 20-14	14	350	3.34	510	910 x 12	158 - 180
HKR 20-16	16	340	3.80	510	910 x 12	180 - 200
HKR 20-18	18	340	4.26	510	910 x 12	198 - 217
HKR 20-20	20	320	4.71	510	910 x 12	220 - 241
HKR 20-22	22		5.17	510	910 x 12	242 - 265
HKR 20-24	24		5.63	510	910 x 12	264 - 289
HKR 20-26	26		6.08	510	910 x 12	286 - 314
HKR 20-28	28		6.54	510	910 x 12	308 - 338
HKR 20-30	30		7.00	510	910 x 12	330 - 362

The Erdvark HKR Extreme H/duty Offset Disc Harrow is ideal for first cut after land clearing, to uplift soil, cut root and cut left over vegetation.

The cutting depth is up to 320 mm and can handle stumps and rocky conditions.

This Disc Harrow is fitted with 36" (910 mm x 12 mm) notched discs and the Erdvark heavy duty bearings with high tensile disc axle of 65 mm in diameter to handle extreme tuff conditions.

The Erdvark HKR is available in disc spacing of 16" (410mm), 18" (460mm) or 20" (510mm) to suite your tractors and ground conditions.

100% Guarantee that no dust and sand can enter bearing unit under normal working conditions due to Floating Duo-cone seals.

Bearing Unit requires no service or any lubrication; it is lubricated with special grease at the factory and sealed.

Wide frame construction with depth control ensures excellent stability in all conditions.



Erdvark maintenance free bearing unit with cutter



For queries, contact:

Willem Oosthuizen

Mobile: +27 (0) 82 498 6619

Email: willem@erdvark.co.za

Nico Botes

Mobile: +27 (0) 82 920 9346

Email: nico@erdvark.co.za

Dennis Green (Factory Trawl)

Mobile: +27 (0) 72 120 9159

Office: +27 (0) 27 216 1536

Email: dennis@erdvark.co.za

Website: www.erdvark.co.za