

OFFSET DISC 3 POINT 22" - DKS

CHARACTERISTICS

1. Ideal for vineyards, fruit orchards and vegetable cultivation.
2. Discs-gangs cutting angles adjustment 16 - 28 degrees.
3. Fitted with 32mm High tensile disc axles with 22" (560mm) plough discs (notched discs in front and plain discs at rear), as well as mud scrapers.
4. Disc spacing is 9" (228mm)
5. Bearing-unit requires no service or lubrication, it is lubricated with a special lubricant at the factory and sealed.
6. No dust and sand can enter bearing-unit under normal working conditions due to Floating Duo-cone Seals.



Erdvark maintenance free bearing unit.



DKS9-12



DKS9-20



DKS9-20



DKS9-12

MODEL NO	DISCS	MASS kg	MASS PER DISC kg	WORKING WIDTH m	DISC SPACING mm	AVERAGE TRACTOR REQ. kW	PRICE VAT EXCL R
DKS9-10	10	460	± 45	1.12	228	30 - 35	59 277
DKS9-12	12	540	± 45	1.35	228	35 - 45	64 088
DKS9-14	14	620	± 45	1.57	228	40 - 50	81 886
DKS9-16	16	640	± 45	1.80	228	45 - 55	91 689
DKS9-18	18	920	± 45	2.03	228	50 - 60	105 567
DKS9-20	20	980	± 45	2.26	228	52 - 68	117 295
DKS9-22	22	1080	± 45	2.48	228	65 - 75	129 020

Prices are VAT excluded and ex-factory and do not include delivery. Erdvark Price List valid until 30 April 2024

Prices and Specifications are subject to change without notice. All price exclude VAT.

Erdvark Implements have a limited guarantee for 1 year from date of purchase.

Willem Oosthuizen
Dennis Green
Nico Botes

Mobile: + 27 (0) 82 498 6619
Mobile: + 27 (0) 72 120 9159
Mobile: + 27 (0) 82 920 9346

Email: willem@erdvark.co.za
Email: dennis@erdvark.co.za
Email: nico@erdvark.co.za